

What is claimed is:

1. A microstrip patch antenna, comprising:

5 a lower patch antenna layer having a dielectric layer and
a ground plane, for radiating energy by exciting current by a
feeding means electrically connected to a lower radiating
patch on a side of the dielectric layer;

10 an upper patch antenna layer having a dielectric film,
for radiating energy by exciting current by the lower
radiating patch electromagnetically connected to an upper
radiating patch on a side of the dielectric film;

15 a foam layer for distancing the upper patch antenna layer
from the lower patch antenna layer by arranging the foam layer
between the lower patch antenna layer and the upper patch
antenna layer; and

a dielectric superstrate located with a predeteremined
distance from the upper patch antenna layer.

20 2. The apparatus as recited in claim 1, wherein the upper
radiating patch is stacked upon the lower radiating patch.

25 3. The apparatus as recited in claim 1, wherein the
thickness and the dielectric constant of the dielectric
superstrate determine the bandwidth and gain of the microstrip
patch antenna.

4. The apparatus as recited in claim 3, wherein as the

thickness of the dielectric superstrate becomes thicker and the dielectric constant of the dielectric superstrate is increased, the gain of the antenna tends to be higher and the bandwidth of the antenna tends to be narrower.

5

5. The apparatus as recited in claim 1, wherein the predetermined distance between the upper patch antenna layer and the dielectric superstrate largely affects the resonant characteristics of the microstrip patch antenna.

10

6. A microstrip array antenna having a plurality of microstrip patch antennas, each of the microstrip patch antenna comprising:

15 a lower patch antenna layer having a dielectric layer and a ground plane, for radiating energy by exciting current by a feeding means electrically connected to a lower radiating patch on a side of the dielectric layer;

20 an upper patch antenna layer having a dielectric film, for radiating energy by exciting current by the lower radiating patch electromagnetically connected to an upper radiating patch on a side of the dielectric film;

25 a foam layer for distancing the upper patch antenna layer from the lower patch antenna layer by arranging the foam layer between the lower patch antenna layer and the upper patch antenna layer; and

a dielectric superstrate located with a predetermined distance from the upper patch antenna layer,

wherein the microstrip array antenna is designed using a corporate feeding method and an element spacing of the microstrip patch antennas is more than $1\lambda_0$ at 12GHz to minimize the coupling between the microstrip patch antennas, 5 wherein although the element spacing in the array is wider than the wavelength at 12GHz in free space, the grating lobes can be reduced by the dielectric superstrate.